



linear dimension(Tolerances Standard GB/T 14486-2008)								—		
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

REVISION RECORD				
REV.	DESCRIPTION	ECN No.	APPROVED	DATE
A	新发行		CLF	22.04.18



UL/CUL 技术参数 UL/CUL Technical Data					
等级 Use Group		B	C	D	
额定电压 Rated Voltage [V]		300	-	300	
额定电流 Rated Current [A]		10	-	10	
接线范围 Wire Range 单/多芯线 Solid/Stranded [AWG]		-			
耐电压 Withstanding Voltage		1600V/1Min			
IEC 技术参数 IEC Technical Data					
过电压类别 Overvoltage Category		III	III	II	
污染等级 Contamination Class		3	2	2	
额定电压 Rated Voltage [V]		-	320	630	
额定电流 Rated Current [A]		-	15	15	
额定冲击电压 Impulse withstand voltage ^a [KV]		-	4.0	4.0	
导线截面积 Conductor cross section 硬质/柔性导线 Solid/flexible [mm ²]		-			
材料 Material					
绝缘材料 Insulation Material		PA66			
阻燃等级 Imflammability		UL94V-0			
导体材料 Contactor Material		铜合金 Copper alloy			
导体表面镀层 Contactive Coating		镀锡 Tin Plated			
一般参数 Other Data					
间距 Pitch [mm]		5.0			
极数 Poles [P]		4			
剥线长度 Stripping Length [mm]		-			
螺丝 Screw/扭矩 Torque(Max) [N.m]		-			
工作温度 Operating temperatur [°C]		-40~+105			
引针尺寸 Pin Dimensions [mm]		3.5			
PCB板孔径 PCB Hole Diameter [mm]		1.6			

DES.	LQQ	DATE	22.04.18	单位/UNITS	mm	尺寸/SIZE	A4	比例/SCALE	1:1	第三视角/THIRD ANGLE PROJECTION	版本/REV	A
CHK.	BY	DATE	22.04.18		慈溪市科发电子有限公司 CIXI KEFA ELECTRONIC CO., LTD				名称/TITLE	KF2EDGLF-5.0		
APP.	CLF	DATE	22.04.18									