






linear dimension(Tolerances Standard GB/T 14486-2008)								—		
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60



PCB Layout



REVISION RECORD				
REV.	DESCRIPTION	ECN No.	APPROVED	DATE
A	新发行		CLF	26.08.04

UL/CUL 技术 参数					
UL/CUL Technical Data					
等 级	Use Group	B	C	D	
额定电压	Rated Voltage	[V]	300	-	-
额定电流	Rated Current	[A]	20	-	-
接线范围	Wire Range	22-10			
单/多芯线	Solid/Stranded				[AWG]
IEC 技术参数					
IEC Technical Data					
额定电压	Rated Voltage	[V]	450		
额定电流	Rated Current	[A]	24		
耐电压	Withstanding Voltage	[V/1Min]	AC2500V/1Min		
导线截面积	Conductor cross section	2.5			
硬质/柔性导线	Solid/ flexible				[mm²]
材 料					
绝缘材料	Insulation Material	PA66			
阻燃等级	Imflammability	UL94V-0			
导体材料	Contactur Material	铜合金 Copper alloy			
导体表面镀层	Contactive Coating	镀锡 Tin Plated			
一般参数 Other Data					
间距	Pitch	[mm]	7.62		
极数	Poles	[P]	02-24		
剥线长度	Stripping Length	[mm]	-		
螺丝	Screw/扭矩 Torque(Max)	[N.m]	M3/0.8		
工作温度	Operating temperatur	[°C]	-40~+105		
引针尺寸	Pin Dimensions	[mm]	5.50		
PCB板孔径	PCB Hole Diameter	[mm]	1.50		

				单位 / UNITS	mm	尺寸 / SIZE	A4	比例 / SCALE	1:1	第三视角 / THIRD ANGLE PROJECTION		版本 / REV	A
DES.	LSW	DATE	26.08.04	慈溪市科发电子有限公司 CIXI KEFA ELECTRONIC CO., LTD						 名称 / TITLE HB762-7.62			
CHK.	SJD	DATE	26.08.04										
APP.	CLF	DATE	26.08.04										